

 CARRO MISCELATORE CON MOTORE DIESEL NELLA PARTE ANTERIORE DESTRA

 MIXER WAGON EQUIPPED WITH FRONT ENGINE ON THE RIGHT SIDE



- Cofano motore apribile, che permette una grande accessibilità al motore diesel al gruppo pompe
- Cabina di guida confortevole e con ampia visibilità
- Trasmissione alle coclee con motore idraulico, riduttore epicicloidale e cassa a bagno d'olio
- Coclee di miscelazione contro-rotanti con contro coltelli sul fondo vasca
- Trazione anteriore a due velocità con sospensioni a balestre
- Fresa anteriore di elevata potenza, con motore idraulico e riduttore epicicloidale
- Tappeto di scarico laterale sinistro
- Pesa elettronica con 4 celle in acciaio inox
- Bonnet can be completely opened, granting full access to the engine and to the pump
- Comfortable driving cab with wide visibility
- Augers' transmission with hydraulic motor, epicyclic reduction gear and oil bath gearbox
- Counter rotating augers with counter-knives welded on the bottom of the tank
- Front drive with travel 2 speeds and leaf springs
- Strong milling cutter, equipped with hydraulic motor and epicyclic reduction gear
- Left discharge conveyor with stainless steel chain
- Electronic weighing system with 4 stainless steel loading cells

| Shuttle | | OR-13 | OR-15 | OR-17 | OR-20 |
|--------------------------------------|------|------------------|-------------------|-------------------|------------------|
| Capacità-Capacity-Capacité | | 13m ³ | 15 m ³ | 17 m ³ | 20m ³ |
| Lunghezza - Length - Longueur | (mm) | 8060 | 8060 | 8590 | 8590 |
| Larghezza - Width - Largeur | (mm) | 2350 | 2450 | 2450 | 2550 |
| Altezza - Height - Hauteur | (mm) | 2900 | 3100 | 3250 | 3450 |
| Peso a vuoto - Weight - Poids a vide | (Kg) | 10600 | 11500 | 12100 | 12500 |
| Motore - Motor - Moteur | (CV) | 140 | 175 | 175 | 185 |

